



Maxell Ltd.

Whitebrook Park, Lower Cookham Road, Maidenhead, Berkshire SL6 8YA United Kingdom - Tel: +44 (0)1628 585 000 - www.maxelldisplay.com

Specifification and photography subject to change.









4K Ultra High Definition Interactive Flat Panel Displays







BUILT IN ANDROID


TEN TOUCH





EASY TO USE MENU

WHITEBOARD APP INCLUDED



MA-6510 | MA-7510 | MA-8610

Available in a range of sizes and two colors to suit any environment, our interactive screens feature crystal clear resolution and highly responsive touch screen technology.

Engage • Involve • Inspire

This smart range of Maxell Interactive flat panel displays incorporate a host of clever features like 10 person multi-touch and have been designed for a variety of uses from boardrooms, classrooms, lecture theatres, foyers, and consultation rooms. The bright LED anti-glare screen, wide viewing angle and two powerful speakers bring presentations to life, with the clean contemporary slim white bezel blending perfectly into most environments, making sure that nothing distracts from the message on the screen. Maxell has it all covered. From the 65" size for huddle meetings through to the largest 86" interactive display for demanding mission-critical applications. With the very latest operating platform capability you can forget time-consuming set-ups and the option of a built-in PC means you don't need any type of external source at all. All you need to do is walk in, turn it on and use.

- Built-in Android with easy to use whiteboard app
- UHD 4K resolution with HDR10
- 10 point Multi-Touch
- Screen Mirroring Wireless Presentation*
- White or Black Bezel Design
- Anti-Glare Tempered Glass
- 3 x HDMI + HDMI Out
- Display Port In + Out
- Windows 10, Linux and Mac Compatible
- Built-in PC Option Available
- VESA Mount included
- Built-in WiFi
- Built-in USB for playback





^{*} Most Windows and Android Devices







These smart new Maxell Interactive Flat Panel Displays have been designed for a variety of uses from boardrooms, classrooms, lecture theatres, foyers and consultation rooms.





Multi-touch Capability for up to Ten People

Maxell's Interactive Flat Panel Displays turn every presentation into an involving experience. Instead of passively viewing, up to 10 people can interact with the screen at the same time, using the supplied stylus pen or their fingers.

Anti-glare Screen

Maxell's Interactive Flat Panel Displays achieve 100% light transmission for outstanding colour, clarity and accuracy — even in direct sunlight.

Useful Features

This range has a host of useful features like built in scheduler, panel lock, advanced colour settings, auto signal turn on and movable Remote Control receiver.

Black or White Bezel *

You can choose which colour model you want depending on your environment.

These model are available in Black or White.

* Depending on your region.

Ensure Best Picture Quality

Ultra HD Resolution achieves the best Image. No distortion and outstanding quality with a wide viewing angle means the user and audience are not compromised in any way. The outstanding resolution of UHD coupled with HDR 10 compatibility vividly delivers high quality images or video content.








Wall Mounting Bracket Included

The supplied bracket allows the units to be safely mounted to most walls without incurring additional expense. As the bracket is a standard VESA mount it's also compatible with the majority of third party trolley manufacturers allowing the unit to be easily moved from room to room.



Connectivity

These Interactive Flat Panels have a number of connectivity solutions: 3 x HDMI, HDMI Out, Display Port In & Out, Computer In and two built in USB ports. Also RS232 control is available via serial port or wired network. Wireless presentation can be used to mirror your contents on the screen with a compatible device.

* Most Windows and Android Devices



The PC module is available as two types; as either built in or as a separate accessory* This PC Module can be connected to a network (wired or wireless), has four USB ports and HDMI output to a second display.

*Region dependent

External Devices

All the range is fully compatible to connect your external devices via HDMI, Display Port or computer in. All these ports will mirror seamlessly your content onto the screen using the micro USB port for interactivity.



Toughened Glass

With 4mm anti-glare glass technology maximising the usability and visability of the screen in bright light conditions, and without shadow. The toughened glass is also fully heat tempered and gives an ultra smooth touch when using the interactivity.

Service and Support

Your Maxell interactive display has been manufactured to the highest standards of care, attention and quality. However if something was to go wrong we offer an on site service* giving you peace of mind in the unlikely event if anything was to go wrong.

*Depending on your region.



Long-lasting Performance

The Interactive Flat Panel Displays really highlights Maxell's reputation for quality and reliability. Its components have been designed and tested for longevity ensuring low running costs and budget savings throughout its lifetime.



Technical Specifications	MA-6510WH (White Colour) MA-651	OWHPC (White Colour with PC) MA-6510BK (Black Colour) MA-6510BKPC (Black Colour with PC)			
Display Size Diagonal (Inch)		65"			
Backlight		Direc	t LED		
Visible Area		1428.48mm (H)	x 803.52mm (V)		
Panel Type		VA			
Screen Response Time z(G to G) (ms)			1		
Max. Resolution		3840	x 2160		
Max. Colours		1.07 Billio	n Colours		
Brightness		350 nit	typical		
Contrast Ratio		400	0:1		
Viewing Angle (H/V)		17	8°		
Supported Resolutions		640 x 480, 800 x 600, 1024 x 768, 1280 x 1400 x 1050, 1440 x 900,			
Supported Signals		VGA, SVGA, XGA, WXGA, Fu	II HD, WUXGA, 4K, HDR 10		
Panel Life Time		Typical 50,	000 hours		
Max Daily Usage		16/7			
V-Frequency		60Hz			
Touch Screen		Infrared (IR) Tech - 10 Points			
Glass		Anti-Glare, Tempered			
Vesa Mount Dimensions		400 x 4	100 M6		
	Digital	x3 HDMI (2.2 HDCP Compli	ant), x1 Display Port (1.2a)		
	Analog	x1 VGA D-	Sub 15-pin		
	Audio	x1 RCA	(L + R)		
Input Terminals	Control (RS-232C)	x1 D-Su			
	USB	x2 USB A, x1 Mid			
	IR	x1 IR			
	LAN	x1 RJ45, x1 Android R	145, x2 RJ12 (Service)		
Output Terminals	Digital Audio	x1 HDMI, x1 Display Port, SPDIF	Optical Out, 3.5mm Headphone		
Wireless		802.11 a/b/	g/n Support		
Speaker		x2	8W		
	Detection Method	Infr	ared		
	Detection Area	1428.48 x	303.52 mm		
	Touch Accuracy	+/- 2 mm			
Touch Panel	Response time	<10ms			
	PC Connector	USB Micro A			
	Driver	Windows multi touch support MAC single touch support Linux			
	Touch Pen	Y	15		
Android Features	Version, Supported, Inputs, Software, Internal Storage	Android, 7.1 MicroSD, USB2.0,	Ethornet Whiteheard Ann. 9 Ch		
	version, supported, impors, software, internal storage				
Power Requirement		110 - 240 V			
Operating/Storage Temperature		0 - 4			
Operating/Storage Humidity		20%			
Power Consumption Dimensions (mm)		65" w/OPS: 200W / 1507 (w) x 882			
vimensions (mm) Weight		1507 (W) X 802			
Colour		Black/WI			
		Remote control, Batteries 2 x AAA, Quick Start Guide, I			
Main Accessories		Micro USB to USB cable, 4 x cable manageme	ent clips, Wall mount, Touch pen, Power lead.		
Optional Accessories		Touch Pen Part No. 1	-STYLUS, PC Module		
Remote Control		Part no: VS			
Certification		CE / R&TTE /RED			
	Mode	MA-OPS7200KL	MA-OPS3865KL		
	СРИ	Intel® Core™ i5-7200U Kaby Lake-U SoC	Intel® Celeron™ 3865U Kaby Lake-U SoC		
	GPU	Intel® HD Graphics 620	Intel® HD Graphics 610		
	GPU Memory	8 GB SO-DIMM DDR4	4 GB SO-DIMM DDR4		
	memory Storage	500 GB HDD	4 OB 50-DIMM DUK4		
PC Module Specification (Two types available as an accessory)	Storage Resolution support	Ultra HD, Max. 4096 x 2160 @60Hz LAN: 10/100 Mbps, WLAN: 802.11 a/g/n, Bluetooth 4.0			
	Kesolution support Network				
	I/O Parts	1x RJ45, 1x RS232, 2x USB 3.0, 2x USB 2.0 , 1xHDMI Out, 1	x Audio in/out, 2x Wi-Fi antenna connector, 1x Power button		
	Features	TPM (Trusted PI	atform Module)		
	Operating System	Window	s 10 Pro		
Warranty		3 or 5 years (Please check with your local dealer)			

MA-7510WH (White Colour) MA-7 MA-7	7510WHPC (White Color 7510BKPC (Black Colour	ur with PC) MA-7510BK (Black Colour) with PC)	MA-8610WH (White Colour) MA-86	510WHPC (White Colour with PC) MA PC (Black Colour with PC	-8610BK (Black Colour) MA-8610BK-
		75"		8	6"
		Direct LED		Edge	LED
		1665.65 mm (H) x 944.73 mm (V)			x 1076mm (V)
		IPS		IPS	
		8			8
		3840 x 2160		3840	x 2160
		10bit (D), 1.07 Billion Colours		10bit (D), 1.07	Billion Colours
		400 nit typical		410 nit	typical
		1400:1		1200:1	
		178°		17	8°
		640 x 480, 800 x 600, 1024 x 768, 1280 x 720, 1280 x 768, 1280 x 960, 1280 x 1024, 1400 x 1050, 1440 x 900, 1920 x 1080, 3840 x 2160		640 x 480, 800 x 600, 1024 x 768, 1280 x 1024, 1400 x 1050, 1440	1280 x 720, 1280 x 768, 1280 x 960, x 900, 1920 x 1080, 3840 x 2160
		VGA, SVGA, XGA, WXGA, Full HD, WUXGA, 4K, HDR 10		VGA, SVGA, XGA, WXGA, FL	II HD WIIYGA AK HDB 10
				Typical 50,000 hours	
		Typical 50,000 hours		Typical 50	,000 hours
		16/7		16	/7
		60Hz		60	Hz
		Infrared (IR) Tech - 10 Points		Infrared (IR) 1	Fech - 10 Points
		Anti Glare, Tempered		Anti Glare,	, Tempered
		600 x 400 M8			400 M8
Digital		x3 HDMI (2.2 HDCP Compliant), x1 Display Port (1.2a)	Digital		ant), x1 Display Port (1.2a)
Analog		x1 VGA D-Sub 15-pin	Analog		Sub 15-pin
Audio		x1 RCA (L + R)	Audio	x1 RCA	
Control (RS-232C)		x1 D-Sub 9-pin	Control (RS-232C)	x1 D-Su	ub 9-pin
USB		x2 USB A, x1 Micro USB for touch	USB	x2 USB A, x1 Mi	cro USB for touch
IR		x1 IR Input	IR	x1 IR	Input
LAN		x1 RJ45, x1 Android RJ45, x2 RJ12 (Service)	LAN	x1 RJ45, x1 Android R	U45, x2 RJ12 (Service)
Digital Audio		x1 HDMI, x1 Display Port, SPDIF Optical Out, 3.5mm Headphone	Digital Audio	x1 HDMI, x1 Display Port, SPDIF Optical Out, 3.5mm Headphone	
		802.11 a/b/g/n Support		802.11 a/b/g/n Support (dongle)	
		х2 12W		оиz.11 a/ в/ g/n зиррогі (aongie) x2 12W	
Detection Method		Infrared	Detection Method	Infrared	
Detection Area		1665.65 x 944.73 mm	Detection Area	1907 x 1076 mm	
Touch Accuracy		+/- 2 mm	Touch Accuracy	+/- 2 mm	
Response time		<10ms	Response time	<10ms	
PC Connector	PC Connector		PC Connector	USB Micro A	
		Windows multi touch support MAC single touch support			
Driver		Linux	Driver	Windows multi touch support, MAC single touch support, Linux	
Touch Pen		Yes	Touch Pen	Yes	
Version Supported Inputs / Software Internal Storage		Android 7.1, MicroSD, USB2.0, Ethernet, Whiteboard	Version Supported Inputs / Software Internal	Android 7.1, MicroSD, USB2.0, Ethernet, Whiteboard App, 8Gb	
Software internal Storag		App, 8 Gb	Storage		
Software internal storage			Storage	110 - 240 V	/50 - 60 Hz
John William Charles		App, 8 Gb	siorage		/50 - 60 Hz 10°C
Sometic mental stang		App, 8 Gb 110 - 240 V /50 - 60 Hz	210rage	0 - 4	
John and Jung		App, 8 Gb 110 - 240 V /50 - 60 Hz 0 - 40°C 20% - 80%	Storage	0 - 4 20%	10°C
John Marie Marie July		App, 8 Gb 110 - 240 V /50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W	Storage	0 - 4 20% 86" w/OPS: 370W,	10°C - 80% - 86″ Display: 310W
John and July		App, 8 Gb 110 - 240 V /50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm	Storage	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146	10°C - 80% . 86° Display: 310W (h) x 103 (d) mm
John and Jung		App, 8 Gb 110 - 240 V /50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 {w} x 1008 {h} x 119 {d} mm 59Kg	Storage	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91	10°C - 80% 86" Display: 310W (h) x 103 (d) mm Kg
John William Jung		App, 8 Gb 110 - 240 V /50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm	Storage	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91	10°C - 80% . 86° Display: 310W (h) x 103 (d) mm
John William July		App, 8 Gb 110 - 240 V /50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 {w} x 1008 {h} x 119 {d} mm 59Kg	Storage	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB coble, 4 x coble managem	10°C - 80% 86" Display: 310W (h) x 103 (d) mm Kg
John and Jung		App, 8 Gb 110 - 240 V /50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, OPS Antenna (if your model includes OPS), Micro US8 10 US8 cable, 4 x coble monagement clips, Woll mount,	Storage	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB coble, 4 x coble managem	10°C - 80% - 86" Display: 310W (h) x 103 (d) mm Kg White Bezel - IR Extender, OPS Antenna (if your model includes ent clips, Wall mount, Touch pen, Power lead, Wi-Fi droid Dongle
John Mary		App, 8 Gb 110 - 240 V /50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, OPS Antenna (if your model includes OPS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch pen, Power lead.	Storage	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB cable, 4 x cable managem Dongle, Anc	10°C - 80% 86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenno (if your model includes ent clips, Wall mount, Touch pen, Power lead, Wi-Fi droid Dongle
John Mary	ge	App, 8 Gb 110 - 240 V /50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, OPS Antenna (if your model includes OPS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch pen, Power lead. Touch Pen Part No. L STYLUS, PC Module	Storage	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB coble, 4 x coble managem Dongle, Anc	10°C -80% 86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenna (if your model includes ent clips, Wall mount, Touch pen, Power lead, Wi-Fi droid Dongle I-STYLUS, PC Module 530085692
	ge CE / R&TTE / RED	App, 8 Gb 110 - 240 V / 50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, OPS Antenna (if your model includes OPS), Micro USB to USB coble, 4 x coble monagement clips, Wall mount, Touch Pen Part No. I-STYLUS, PC Module Part no: VS30085692		0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB cable, 4 x cable managem Dongle, Anc Touch Pen Part No. Part no: VS	10°C - 80% - 86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenna (if your model includes ent clips, Wall mount, Touch pen, Power lead, Wi-Fidroid Dongle 1-STYLUS, PC Module 530085692 TIE / RED
Mode	ge CE / R&TTE / RED MA-0PS7200KL Intel® Core™ 15-7200U Kuby	App, 8 Gb 110 - 240 V /50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, OPS Antenna (if your model includes OPS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch pen, Power lead. Touch Pen Part No. L STYLUS, PC Module	Storage Mode CPU	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB coble, 4 x coble managem Dongle, Anc	10°C -80% 86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenna (if your model includes ent clips, Wall mount, Touch pen, Power lead, Wi-Fi froid Dongle I-STYLUS, PC Module 530085692
Mode CPU	CE / R&TTE /RED MA-0FS7200KL Intel® Core™ 15-7200U Kaby Lake-U 5oC	App, 8 Gb 110 - 240 V / 50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, OPS Antenna (if your model includes OPS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch Pen, Power lead. Touch Pen Part No. I-STYLUS, PC Module Part no: VS30085692 MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC	Mode CPU	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB cable, 4 x cable managem Dongle, Anc Touch Pen Part No. I Part no: VS CE / R& MA-OPS7200KL Intel® Core™ i5-7200U Kaby Lake-U SoC	10°C -80% 86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenna (if your model includes ent clips, Woll mount, Touch pen, Power lead, Wi-Fi droid Dongle 1-STYLUS, PC Module 530085692 TTE /RED MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC
Mode	CE / R&TTE / RED MA-0PS7 ZOOKL Intel® Core™ 15-7200U Kaby Lako-U SoC Intel® HD Graphics 620	App, 8 Gb 110 - 240 V / 50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, OPS Antenna (if your model includes OPS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch pen, Power lead. Touch Pen Part No. I-STYLUS, PC Module Part no: VS30085692 MA-OPS3865KL Intel® Celeron™ 3865U Kaby Loke-U SoC Intel® HD Graphics 610	Mode	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB coble, 4 x cable managem Dongle, Anc Touch Pen Part No. Part no: VS CE / R& MA-OPS7200KL Intel® Core™ is-7200U Kaby Lake-U SoC Intel® HD Graphics 620	10°C -80% -86" Display: 310W (h) x 103 (d) mm Kg White Bezel -, IR Extender, OPS Antenna (if your model includes ent clips, Wall mount, Touch pen, Power lead, Wi-Fi droid Dongle I-STYLUS, PC Module 530085692 TIE /RED MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® HD Graphics 610
Mode CPU	CE / R&TTE /RED MA-0FS7200KL Intel® Core™ 15-7200U Kaby Lake-U 5oC	App, 8 Gb 110 - 240 V / 50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, OPS Antenna (if your model includes OPS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch Pen, Power lead. Touch Pen Part No. I-STYLUS, PC Module Part no: VS30085692 MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC	Mode CPU	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB cable, 4 x cable managem Dongle, Anc Touch Pen Part No. I Part no: VS CE / R& MA-OPS7200KL Intel® Core™ i5-7200U Kaby Lake-U SoC	10°C -80% 86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenna (if your model includes ent clips, Woll mount, Touch pen, Power lead, Wi-Fi droid Dongle I-STYLUS, PC Module 530085692 TTE /RED MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC
Mode CPU GPU	CE / R&TTE / RED MA-0PS7 ZOOKL Intel® Core™ 15-7200U Kaby Lako-U SoC Intel® HD Graphics 620	App, 8 Gb 110 - 240 V / 50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, OPS Antenna (if your model includes OPS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch pen, Power lead. Touch Pen Part No. I-STYLUS, PC Module Part no: VS30085692 MA-OPS3865KL Intel® Celeron™ 3865U Kaby Loke-U SoC Intel® HD Graphics 610	Mode CPU GPU	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB coble, 4 x cable managem Dongle, Anc Touch Pen Part No. Part no: VS CE / R& MA-OPS7200KL Intel® Core™ is-7200U Kaby Lake-U SoC Intel® HD Graphics 620	10°C .80% .86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenna (if your model includes ent clips, Well mount, Touch pen, Power lead, Wi-FT droid Dongle LSTYLUS, PC Module .330085692 TTE / RED MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® HD Graphics 610
Mode CPU GPU Memory	CE / R&TTE / R&D MA-OPS7200KL Intel® Core™ 15-7200U Kaby Lake-U SoC Intel® HD Graphics 620 8 GB SO-DIMM DDR4 500 GB HDD	App, 8 Gb 110 - 240 V /50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, OPS Antenna (if your model includes OPS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch pen, Power lead. Touch Pen Part No. 1-STYLUS, PC Module Part no: VS30085692 MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® HD Graphics 610 4 GB SO-DIMM DDR4	Mode CPU GPU Memory	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB cable, 4 x cable managem Dongle, Anc Touch Pen Part No. I Part no: VS CE / R& MA-OPS7200KL Intel® Core™ i5-7200U Kaby Lake-U SoC Intel® HD Graphics 620 8 GB SO-DIMM DDR4 500 GB HDD	10°C .80% .86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenno (if your model includes ent clips, Wall mount, Touch pen, Power lead, Wi-Fi droid Dongle I-STYLUS, PC Module .30085692 ITE /RED MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® HD Graphics 610 4 GB SO-DIMM DDR4
Mode CPU GPU Memory Storage	CE / R&TTE / RED MA-0FS7200KL Intel® Core™ 15-7200U Kaby Lake-U 5oC Intel® HD Graphics 620 8 GB SO-DIMM DDR4 500 GB HDD	App, 8 Gb 110 - 240 V / 50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, 0PS Antenna (if your model includes OPS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch Pen Part No. I-STYLUS, PC Module Part no: VS30085692 MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® AGB SSD HD, Max. 4096 x 2160 @60Hz	Mode CPU GPU Memory Storage	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB cable, 4 x cable managem Dongle, Anc Touch Pen Part No. I Part no: YS CE / R& MA-OPS7200KL Intel® Core™ i5-7200U Kaby Lake-U SoC Intel® HD Graphics 620 8 GB SO-DIMM DDR4 500 GB HDD Ultra HD Max. 4	10°C -80% 86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenna (if your model includes ent clips, Woll mount, Touch pen, Power lead, Wi-Fi droid Dongle 1-STYLUS, PC Module 530085692 TTE /RED MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® HD Graphics 610 4 GB SO-DIMM DDR4 64GB SSD
Mode CPU GPU Memory Storage Resolution support Network	CE / R&TTE / RED MA-0PS7200KL Intel® Core™ 15-7200U Kaby Lako-U SoC Intel® HD Graphics 620 8 GB SO-DIMM DDR4 500 GB HDD Ultra LAN: 10/100 M	App, 8 Gb 110 - 240 V / 50 - 60 Hz 0 - 40°C 20% - 80% 75" w / 0PS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries: 2 x AAA, Quick Start Guide, IR Extender, 0PS Antenna (if your model includes 0PS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch Pen Part No. I-STYLUS, PC Module Part no: VS30085692 MA-0PS3865KL Intel® Celeron™ 3865U Kaby Loke-U SoC Intel® HD Graphics 610 4 GB S0-DIMM DDR4 64GB SSD HD, Max. 4096 x 2160 @60Hz Lbps, WLAN: 802.11 a/g/n, Bluetooth 4.0	Mode CPU GPU Memory Storage Resolution support	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB coble, 4 x cable managem Dongle, Anc Touch Pen Part No. I Part no: VS CE / R& MA-OPS7200KL Intel® Core™ i5-7200U Kaby Lake-U SoC Intel® HD Graphics 620 8 GB SO-DIMM DDR4 500 GB HDD Ultra HD Max. 44 LAN: 10/100 Mbps, WLAN: 4	10°C -80% 86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenna (if your model includes ent clips, Wall mount, Touch pen, Power lead, Wi-Fildroid Dongle I-STYLUS, PC Module 530085692 TIE /RED MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® HD Graphics 610 4 GB SO-DIMM DDR4 64GB SSD 096 x 2160 @60Hz 802.11 a/g/n, Bluetooth 4.0
Mode CPU GPU Memory Storage Resolution support Network	CE / R&TTE / RED MA-OPS7200KL Intel® Core™ 15-7200U Kaby Lake-U 5oC Intel® HD Graphics 620 8 GB SO-DIMM DDR4 500 GB HDD LAN: 10/100 M 1 x RJ45, 1 x RS232, 2x USB 3.0, 2	App, 8 Gb 110 - 240 V / 50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, 0PS Antenna (if your model includes OPS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch Pen Part No. I-STYLUS, PC Module Part no: VS30085692 MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® AGB SSD HD, Max. 4096 x 2160 @60Hz	Mode CPU GPU Memory Storage Resolution support	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB cable, 4 x cable managem Dongle, Anc Touch Pen Part No. I Part no: YS CE / R& MA-OPS7200KL Intel® Core™ i5-7200U Kaby Lake-U SoC Intel® HD Graphics 620 8 GB SO-DIMM DDR4 500 GB HDD Ultra HD Max. 4	10°C -80% 86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenna (if your model includes ent clips, Wall mount, Touch pen, Power lead, Wi-Fidroid Dongle 1-STYLUS, PC Module 530085692 TTE /RED MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® HD Graphics 610 4 GB SO-DIMM DDR4 64GB SSD 096 x 2160 @60Hz 802.11 a/g/n, Bluetooth 4.0 Al Out, 1x Audio in/out, 2x Wi-Fi antenna connector,
Mode CPU GPU Memory Storage Resolution support Network	CE / R&TTE / RED MA-0PS720KL Intel® Core™ 15-7200U Kaby Lake-U SoC Intel® HD Graphics 620 8 GB So-DIMM DDR4 500 GB HDD Ultra LAN: 10/100 M 1x RJ45, 1x RS232, 2x USB 3.0, 2	App, 8 Gb 110 - 240 V / 50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, OPS Antenna (if your model includes OPS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch Pen, Power lead. Touch Pen Part No. I-STYLUS, PC Module Part no: VS30085692 MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® HD Graphics 610 4 GB SO-DIMM DDR4 64GB SSD HD, Max. 4096 x 2160 @60Hz Libs, WLAN: 802.11 a/g/n, Bluetooth 4.0	Mode CPU GPU Memory Storage Resolution support	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB cable, 4 x cable managem Dongle, Anc Touch Pen Part No. Part no: VS CE / R& MA-OPS7200KL Intel® Core™ i5-7200U Kaby Lake-U SoC Intel® HD Graphics 620 8 GB SO-DIMM DDR4 500 GB HDD Ultra HD Max. 4 LAN: 10/100 Mbps, WLAN: 1 1x RJ45, 1x RS232, 2x USB 3.0, 2x USB 2.0, 1xHDM	10°C .80% .86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenna (if your model includes ent clips, Wall mount, Touch pen, Power lead, Wi-Fi droid Dongle LSTYLUS, PC Module .530085692 TITE /RED MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® HD Graphics 610 4 GB SO-DIMM DDR4 64GB SSD .096 x 2160 @60Hz 802.11 a/g/n, Bluetooth 4.0 All Out, 1x Audio in/out, 2x Wi-Fi antenna connector, or button
Mode CPU GPU Memory Storage Resolution support Network 1/O Parts	CE / R&TTE / RED MA-0PS720KL Intel® Core™ 15-7200U Kaby Lake-U SoC Intel® HD Graphics 620 8 GB So-DIMM DDR4 500 GB HDD Ultra LAN: 10/100 M 1x RJ45, 1x RS232, 2x USB 3.0, 2	App, 8 Gb 110 - 240 V / 50 - 60 Hz 0 - 40°C 20% - 80% 75" w/OPS: 300W, 75" Display: 270W 1731 (w) x 1008 (h) x 119 (d) mm 59Kg Black or White Bezel Remote control, Batteries 2 x AAA, Quick Start Guide, IR Extender, 0PS Antenna (if your model includes 0PS), Micro USB to USB cable, 4 x cable management clips, Wall mount, Touch Pen Part No. I-STYLUS, PC Module Part no: VS30085692 MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® AGB SoD DIMM DDR4 64GB SSD HD, Max. 4096 x 2160 @60Hz laps, WLAN: 802.11 a/g/n, Bluetooth 4.0 tx USB 2.0, 1xHDMI Out, 1x Audio in/out, 2x Wi-Fi antenna connector, 1x Power button	Mode CPU GPU Memory Storage Resolution support Network 1/0 Parts	0 - 4 20% 86" w/OPS: 370W, 1975 (w) x 1146 91 Black or W Remote control, Batteries 2 x AAA, Quick Start Guid OPS), Micro USB to USB coble, 4 x coble managem Dongle, Anc Touch Pen Part No. Part no: VS CE / R& MA-OPS7200KL Intel® Core™ 15-7200U Kaby Lake-U SoC Intel® HD Graphics 620 8 GB SO-DIMM DDR4 500 GB HDD Ultra HD Max. 4 LAN: 10/100 Mbps, WLAN: 1 1x RJ45, 1x RS232, 2x USB 3.0, 2x USB 2.0, 1x HDN 1x Powe TPM (Trusted Pl	10°C .80% .86" Display: 310W (h) x 103 (d) mm Kg White Bezel e, IR Extender, OPS Antenna (if your model includes ent clips, Wall mount, Touch pen, Power lead, Wi-Fi droid Dongle LSTYLUS, PC Module .530085692 TITE /RED MA-OPS3865KL Intel® Celeron™ 3865U Kaby Lake-U SoC Intel® HD Graphics 610 4 GB SO-DIMM DDR4 64GB SSD .096 x 2160 @60Hz 802.11 a/g/n, Bluetooth 4.0 All Out, 1x Audio in/out, 2x Wi-Fi antenna connector, or button