

MC-TW3506

Interactive Ultra Short Throw **3LCD Projector**





Introducing our interactive 3LCD MC-TW3506 projector, which combines all our technical expertise with our market leading knowledge.

This easy to install, interactive 3LCD ultra short throw projector gives a brightness of 3700 ANSI lumens. The compact, lightweight design, integrates a powerful 20,000:1 contrast ratio with a WXGA resolution, providing clarity on images even within very bright / light environments.

Key Features:

WXGA 1280 x 800 resolution

3700 ANSI lumens/Colour light output

20,000:1 contrast ratio

Images up to 100" diagonal

Digital zoom and powered focus

3 year/6 month warranty*


Please note: Content, technical specifications and images are subject to change.

*For education and extended warranties please contact your local dealer.

MC-TW3506 Interactive Ultra Short Throw 3LCD Projector Technical Specifications				
Panel Size	3LCD 15mm (0.59")		Analogue Input	15-pin Mini-D-Sub
Panel Structure	3LCD		Video Output	15 pin Mini D-Sub
Resolution	WXGA (1280 x 800)	Ī	Audio Input	3.5mm Stereo Min
Light Output (Brightness) ANSI Lumens	3700 (Normal)		Audio Output	3.5mm Stereo Min
			RS-232C Control	1 x 9-pin D-Sub
Contrast Ratio	20,000:1		Wireless LAN	USB-WL-11N wirele
Lamp Life (Hours)	4000 (Normal), 6000 (Eco-2)		Wired LAN	RJ45 connector x 1
Lens	Built-in		USB Type A	USB Type A x 2 (PC
Number of Colours	16.7 million colours			adapter)
Lens Zoom	Digital Zoom x 1.35		USB Type B	USBType Bx1 (USB)
Lens Focus	Powered Focus		Power Supply	AC 100V – 120V / A
Projection Lens F Number	1.6		Operating Power Consumption	360W
Focus Distance Distance to Width Ratio /	0.41m – 0.69m (centre of glass to screen) 0.3		Standby Power Consumption	Less than 0.35W
Throw Ratio (:1)			Weight	4.4Kg
Diagonal Display Size	60 – 100"		Dimensions (W x H x D)	382 x 141 x 362mm
Installation	Ceiling, Tabletop, Rear	ŀ	Noise (Normal)	37dB (Normal), 32d
Speakers	16W mono		Filter Life (Hours)	4000 Hours
Digital Keystone Correction (Degrees)	Horizontal ± 5°, Vertical ± 5°	ŀ	Tittol Elic (Illula)	CEMarking,EN6100
Picture Modes	Normal, Cinema, Dynamic, Board (Black), Board (Green), Whiteboard, Daytime, Photo, DICOM SIM		Certification	(Class A), EN55024 (Low Voltage Direc
Picture Adjustments	ASPECT selection (Normal / 4:3 / 16:9 / 16:10 / 14:9 / Zoom/Native), Perfect Fit (4 corners and 4 sides), FrameLock(Datasignal with vertical frequency of 49 to 51 Hz, 59 to 61 Hz), HDCR, Image blank by RS232C/		Computer	IBMCompatibleVG SXGA/SXGA+/UXG
			Video	525i (480i), 525p (48 1125i (1080i@50/6
Operating Features	Remotecontrol, Image Optimizer, Magnify, Mirrorreverse image, Up-side down image Keystone V/H, Perfect Fit, Standby Audio, Audiopass through, Cloning function, Easy schedule setting, Auto-Calibration, Fingertouch (Optional), Multi-Display (up to 2 projectors), PC-Less interactive, Driver-less Wireless Capability (Option), Multi-Projector, Moderator		Supplied Accessories	PowerCable (4.5m) USB Cable (5m) x1, AAA Batteries x4, If AA Batteries x2, Ca (fornetwork,etc.)x1,, model)x1,CDUserMa Adapter Cover x1
Network Features Security Features	whitelesscapability(cption), multiproject.coi, who delator ControlMode, ProjectorQuickConnection(ios/Android app), ProjectorMonitoring and Controlfroma Remote Location, E-mail Alerts Password/Myscreen Password, Pin Lock, Key Lock		Optional Accessories	USB-WL-5G, Wall m WM05 (Low ceiling TT-03 Table Top Kit adaptor) HAS-WB0
Supported Languages	34Languages (English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkey, Arabian, Persian, Czech, Danish, Hungarian, Romanian, Slovenian, Croatian, Greek, Lithuanian, Estonian, Latvian, Thai, Portuguese (Brazil), Indonesian, Vietnamese, Hebrew)	İ	Remote Control	HL03033
			Replacement Lamp / Filter	DT01411 / UX3719
			Projector / Lamp Warranty	3 years/6 months (warranties please of

HDMI x 2 (HDCP compliant)

ecifications				
Analogue Input	15-pin Mini-D-Sub x 2, RCA Jack x 1			
Video Output	15 pin Mini D-Sub x 1			
Audio Input	3.5mm Stereo Mini Jack x 2, RCA Jack (L/R) x 1			
Audio Output	3.5mm Stereo Mini Jack x 1			
RS-232C Control	1 x 9-pin D-Sub			
Wireless LAN	USB-WL-11N wireless adaptor (optional)			
Wired LAN	RJ45 connector x 1			
USB Type A	USB Type A x 2 (PC less presentation or wireless adapter)			
USB Type B	USBTypeBx1 (USB display or USB mouse control)			
Power Supply	AC 100V – 120V / AC 220V – 240V (50/60Hz)			
Operating Power Consumption	360W			
Standby Power Consumption	Less than 0.35W			
Weight	4.4Kg			
Dimensions (W x H x D)	382 x 141 x 362mm			
Noise (Normal)	37dB (Normal), 32dB (Eco), 28dB (Eco-2)			
Filter Life (Hours)	4000 Hours			
Certification	CEMarking, EN61000-3-2, EN61000-3-3, EN55032 (Class A), EN55024 (EMC Directive), EN60950-1 (Low Voltage Directive), WEEE/RoHS compliant			
Computer	IBMCompatibleVGA,SVGA,XGA,WXGA,WXGA+/ SXGA/SXGA+/UXGA (compressed)			
Video	525i (480i), 525p (480p), 625i(576i), 625p (576p), 1125i (1080i@50/60), 1125p (1080p@50/60)			
Supplied Accessories	PowerCable (4.5m) x1, Computer Cable (5.0m) x1, USB Cable (5m) x1, Interactive Pen x2, Pen Tip x4, AAA Batteries x4, IR Remote Control Unit x1, AA Batteries x2, Cable Cover x1, Application CD (fornetwork, etc.) x1, Application DVD (for interactive model) x1, CDU ser Manual x1, Concise User Manual x1, Adapter Cover x1			
Optional Accessories	USB-WL-5G, Wall mount unit: HAS-WM03, HAS- WM05 (Low ceiling wall mount), TT-03 Table Top Kit, HAS-WB01 (XGA mount adaptor) HAS-WB0, FT-01B (Finger Touch Unit)			
Remote Control	HL03033			
Replacement Lamp / Filter	DT01411 / UX37191 (Hybrid)			
Projector / Lamp Warranty	3 years/6 months (for education and extended warranties please contact your local dealer)			



Dealer Stamp



Digital Input