



Fig. Wall safe AMS0600, hinge right K-Lock Cawi 2 keys (95 mm), 1 shelf

AMS1001RK / AMS1001RE



EN1143-1 **Burglary** protection



Grade I







4102 (light fire protection)



Domestic insurable up to EUR 65.000



Please add 10 mm to the listed outside depth for mountings

Commercial insurable up to EUR 20.000

[Type AMS] [Wall safes]

AMS series wall safes are designed for installation into suitable masonry. They are set into the wall so that the front (the door) is aligned with the wall and the body is encased with a minimum of 10 cm of concrete. The optional rear wall armouring allows a wall thickness equivalent to the safe depth.

[Product information]

DIN right (internal) - model designation R Hinge

option: DIN left

Door opening angle 95°

Body hot galvanised steel plate construction to resist corrosion

Door structure triple-walled, massive steel design, internal boltwork protected by sheets of

hardened steel to give extra anti-drill resistance

Locking mechanism three-way moving boltwork with large steel bolts protected by additional emer-

gency re-lockers, continuous fixed full height bolt on the hinge side

Colour inside and outside RAL 7035 light grey (powder coated)

Lock model designation K - double-bit lock VdS class 1, Cawi 2 keys (95 mm)

> model designation E - electronic lock VdS class 2, M-locks EM3520 option: other lock models (primary lock or possible secondary lock)

Equipment shelf adjustable (height setting 80 mm)

option: additional shelf

option (only at models with outside depth 380 mm): inside locker

Accessories option: rear wall armor, interior lighting

models AMS0401, AMS0601, AMS0801, AMS1001 do not offer enough depth Note

for file folders DIN A4, one file folder can be stored behind the door

Model Outside dimensions Inside dimensions SH Volume Weight h x w x d (mm)hxwxd(mm) (I) (appr. kg)

900 x 460 x 145


AMS0400RK / AMS0400RE 410 x 510 x 380 360 x 460 x 295 1 49 50 AMS0401RK / AMS0401RE 410 x 510 x 230 360 x 460 x 145 1 24 45 AMS0600RK / AMS0600RE 590 x 510 x 380 540 x 460 x 295 1 73 65 AMS0601RK / AMS0601RE 590 x 510 x 230 540 x 460 x 145 1 36 60 AMS0800RK / AMS0800RE 770 x 510 x 380 720 x 460 x 295 1 98 80 AMS0801RK / AMS0801RE 770 x 510 x 230 720 x 460 x 145 1 48 70 2 122 AMS1000RK / AMS1000RE 950 x 510 x 380 900 x 460 x 295

950 x 510 x 230

95 2 60 85

[Equipment options]







AMS0600 AMS0800