







Burglary protection according to safe type



according to safe type



4102 (light fire protection)



Domestic insurable according to safe type



Commercial insurable according to safe type

[Drop-in equipment LBE150]

Construction massive steel structure with security blocking system

Weight appr. 28 kg

Position front, back, back protruding or upon request

Colour inside and outside RAL 7037 dusty grey (always ident with safe colour)

option: special colour according to RAL

Lock cylinder lock with 5 keys

option: further keys upon request

Drop-in goods flexible envelopes max. DIN A4, max. 15 mm thick or

cassettes with max. size 240 x 180 x 60 mm

Accessories option: zipp-bag, cassette



Fig. Zipp-bag

[Deposit safes – drop in safes]

Safes with drop-in equipment offer a simple and secure depositing of e.g. daily cash receipts and are mainly used if more than one person deposit values (e.g. petrol stations, fast food and convenience stores).

- Drop-in goods (e.g. zipp-bag) are deposited through the drop-in flap into the safe.
- A security anti-fishing device prevents the later removal of a deposited bag.
- The deposited bags can only be removed by the manager of the safe.

[Product information]

All Wertheim standing safes in grade I, II and III can be equipped with a drop-in mechanism LBE150. According to the requested insurance class and the capacity of bags, the right safe can be chosen. Please note, that deposit safes are certified according to security class VSÖ — all other certifications expire due to the opening of the drop-in mechanism. VDMA-safes with drop-in mechanism are delivered without certification label.

[Example deposit safe AM25RE]

Security class burglary protection according to EN1143-1, VSÖ: Class EN 1

Hinge DIN right – model designation R

option: DIN left

Door opening angle 180°

Body double-walled, filled with high resistant barrier material

Door structure triple-walled, filled with high resistant barrier material,

internal boltwork protected by sheets of hardened steel

to give extra anti-drill resistance

Locking mechanism three-way moving boltwork with large steel bolts,

protected by additional emergency re-lockers, continuous fixed full height bolt on the hinge side

Anchoring prepared for floor and rear wall anchoring anchoring bolts and shields are supplied

option: additional anchoring holes (customer specifies position)

Alarm connection VdS-certified cable channels to allow connection to a burglar alarm system

Colour inside and outside RAL 7037 dusty grey

option: special colour according to RAL

Lock model designation E – electronic lock VdS class 2, M-locks EM3520

option: other lock models (primary lock or possible secondary locks)

Equipment it is recommended to install no internal equipment in deposit safes

Accessories option: certified steel plinth to raise the level of the safe,

fire protection door rebate seals, alarm switch set, interior lighting

Drop-in position front and center

option: on the back, on the back protruding, other options upon request

Maximum volume subject to bag filling, position of drop-in equipment etc.