



Fig. Swing-in door safe BWP1902, double-doored, special colour RAL 7016 anthracite grey E-Lock La Gard Combogard PRO, 60 deposit boxes with electronic cylindric lock

Outside dimensions

1864 x 1416 x 688

h x w x d (mm)

Model

BWP1902K / BWP1902E



EN1143-1 Burglary protection



Grade II



Grade I



Class EN 2



4102 (light fire protection)



Domestic insurable up to EUR 100.000



Commercial insurable up to EUR 50.000

[Swing-in door safes]

[Type BWP]

BWP series safes are fitted with swing-in doors. They are ideal for facilities (e.g. deposit boxes) where doors remain open during working hours and doors do not hinder. This safe does not have to be anchored.

[Product information]

Hinge double-doored

Door opening swing-in doors – upon opening, the doors slide into the side of the safe, leaving

the area in front of the safe completely free – several safes can be positioned next to each other in a row, without open doors interfering each other

Body triple-walled, filled with armoured, high resistant barrier material

Door structure triple-walled, with armoured, high resistant barrier material, internal boltwork

protected by sheets of hardened steel to give extra anti-drill resistance

Locking mechanism three-way moving boltwork with large steel bolts protected by additional emer-

gency re-lockers, continuous fixed full height bolt on the hinge side

Anchoring fitted for floor anchoring

option: additional anchoring holes (customer specifies position)

Alarm connection VdS-certified cable channels to allow connection to a burglar alarm system

Colour inside and outside RAL 7035 light grey

option: special colour according to RAL

Lock model designation K – double-bit lock VdS class 1, Cawi 2 keys (95 mm)

model designation E — electronic lock VdS class 2, M-locks EM3520 option: other lock models (primary lock or possible secondary lock)


Equipment option: shelf, inside locker, drawer, pull-out shelf,

deposit boxes (upon request)

Accessories option: alarm switch set, interior lighting

[Equipment options]





Please add 20 mm to the listed outside depth for mountings.

Volume

(I)

935

Weight

1250

(appr. kg)

Inside dimensions

h x w x d (mm)

1730 x 960 x 563

BWP1902 with shelves

BWP1902 with deposit boxes